


Camouflaged Concrete Corp.
P.O. Box 51
Farmersville, Tx 75442
800 / 650 - 1157
903 / 776-2539 Fax
www.ConcreteCamouflage.com
2/25/2005

Camouflaged Concrete Corp.
Manufactures of Quality Decorative Concrete Products.



Product Guide / Specification Sheet

Notes: This specification sheet is written in accordance with the Construction Specifications Institute 3 - Part Format., contained in the CSI Manual of Practice.

Attention: Must be carefully reviewed and edited by Architect to meet the requirements of the project and local building codes. Coordinate this section with other specification sections and the drawings.

Delete all "Notes" when editing section.

SECTION 09695 FLOOR WAX

Notes: This section covers Concrete Camouflage TOP SHIELD Wax for interior use on any sealed surface.

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Wax for interior [concrete] [other] Floor or surface..

1.2 RELATED SECTIONS

Notes: Edit the following list of related sections as required for the project. List other sections with work directly related to this section.

- A. Section 03300 - Cast in Place Concrete.
- B. Section 09930 - Stains and Transparent Finishes.

1.3 SUBMITTALS

- A. Comply with Section 01330 - Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including surface preparation and application instructions.
- C. Maintenance Instructions: Submit manufacturer's maintenance and cleaning instructions.

1.4 QUALITY ASSURANCE

A. Single Source Responsibility: Concrete stain, floor sealer, and floor wax products shall be of a single manufacturer.

1.5 DELIVERY, STORAGE, AND HANDLING

A. Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying manufacturer and product name.

B. Storage: Store materials in a clean, dry area indoors in accordance with manufacturer's instructions. Keep containers sealed until ready for use. Keep away from ignition sources. Do not allow to freeze.

C. Handling: Protect materials during handling and application to prevent damage, contamination, or injury.

1.6 ENVIRONMENTAL REQUIREMENTS

A. Floor Wax: Do not apply when air or surface temperature is below 50 degrees F.

B. Exterior Surfaces: Do not apply materials in wet weather. Do not apply sealer in extreme heat.

PART 2 PRODUCTS

2.1 MANUFACTURER

A. Camouflaged Concrete Corp., PO Box 51, Farmersville, Texas 75442. Phone (800) 650 1157. Fax (903) 776 2539. Web Site www.ConcreteCamouflage.com. E-Mail info@concretecamouflage.com

2.2 FLOOR WAX

- A. Concrete Sealer: Concrete Camouflage TOP SHIELD Floor Wax
1. Acrylic - water based wax. Can be applied up to 100 times before need to strip.
 2. Non yellowing. Extremely durable and scuff resistant.
 3. Mop on style. No need to buff. Or can be used with commercial machines.
 4. Gloss Finish. Low Maintenance.
 5. More Traction than sealer alone.
 6. Quick drying.
 7. Industrial grade.

PART 3 EXECUTION

3.1 EXAMINATION

A. Examine surfaces to receive wax. Notify Architect if surfaces are not acceptable. Do not begin surface preparation or application until unacceptable conditions have been corrected.

3.2 SURFACE PREPARATION

A. Prepare concrete surface in accordance with manufacturer's instructions.

B. Ensure surface is structurally sound, clean and dry. Free from dirt, oil, and all other surface contaminants.

3.3 APPLICATION

- A. Apply Floor Wax in accordance with manufacturer's instructions at locations indicated on the drawings.
- B. Keep material containers closed when not in use to avoid contamination and spills.

3.4 PROTECTION

- A. Protect finished waxed floors from damage during construction.
- B. Protect finished waxed floors from foot traffic a minimum of 12 hours.
- C. Keep clean with water. Use a mild detergent if needed. Reapply the wax as needed. Use only Concrete Camouflage TOP SHIELD Wax.

END OF SECTION